

Threaded Rod (Material Grade 4.6, 5.6, EN8, EN19, (8.8, 10.9, 12.9)

HSN / SAC : 73181900

Test Method : (EG-ASTM B633 SC2) , (HDG-ASTM A153/A153M)



KANDA BROTHERS

Sr. No	Size	Specification dia.		Specification Length						Standard Packing			Approx Weight			Coating Thickness	
		Diameter (mm)		1000mm		2000mm		3000mm		Approx Per Bundle			Per Pcs Kgs			ZINC (EG)	HDG (Gal.)
		Min	Max	Min	Max	Min	Max	Min	Max	1000mm	2000mm	3000mm	1000mm	2000mm	3000mm		
1	M6	5.79	5.97	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	300	150	100	0.168	0.354	0.531		5
2	M8	7.76	7.97	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	160	85	55	0.310	0.638	0.957		0
3	M10	9.73	9.97	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	105	55	35	0.488	1.004	1.506	7	-
4	M12	11.70	11.97	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	70	36	25	0.705	1.456	2.184	8	6
5	M14	13.70	13.96	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	51	26	17	0.980	1.960	2.940		0
6	M16	15.68	15.96	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	40	20	13	1.310	2.660	3.990	M	M
7	M18	17.62	17.96	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	31	15	10	1.630	3.300	4.950	i	i
8	M20	19.62	19.96	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	25	12	8	2.040	4.160	6.240	c	c
9	M22	21.62	21.96	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	20	10	7	2.530	5.120	7.680	r	r
10	M24	23.58	23.95	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	17	8	6	2.980	6.000	9.000	o	o
11	M27	26.55	26.94	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	13	6	6	3.850	7.700	8.940	n	n
12	M30	29.40	29.90	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	10	5	4	4.690	9.380	11.550	M	M
13	M33	32.30	32.30	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	8	5	4	5.780	11.560	14.070	i	i
14	M36	35.20	35.88	995.8	1005.5	1992.5	2007.5	2989.5	3010.5	7	4	3	6.870	13.740	17.340	n	n